



Small, Rechargeable
Batteries



Large Batteries



Complex Battery
Contacts

UNIVERSAL Battery Adapters

[CADEX.COM/ADAPTERS](https://www.cadex.com/adapters)

1 SELECT YOUR BATTERY TYPE



Smartphone or small rechargeable battery



Large batteries



Narrow and awkwardly placed battery contacts

2 CHOOSE YOUR BATTERY ADAPTER

RigidArm™

The 4-wire RigidArm™, spring-loaded arms lock into position for repetitive testing. A retractable floor holds batteries vertically or horizontally. Simple cable connections offer easy polarity selection, and temperature sensor ensure safe operation.

Part No: 07-110-0192

SmartCable

The Smart Cable features 4-wire battery cables with alligator clips to provide easy connection to larger batteries. Ideal for batteries with exposed tabs or special terminals. The insulated alligator clops are connected to your Cadex analyzer by banana plugs. A magnetized temperature sensor is included.

Part No: 07-110-0115

FlexArm™

The FlexArm™ features battery contacts on flexible, spring-loaded arms to reach narrow and awkwardly placed battery contacts. Magnetic guides on the insulated steel floor hold the battery in any position. Banana plugs enable easy polarity selection. A spring-loaded temperature sensor is embedded in the floor.

Part No: 07-110-0180

3 CHOOSE ANY ANALYZER



C5100 STOREFRONT ANALYZER

More at CADEX.COM/C5



C7X00 PROFESSIONAL ANALYZER

More at CADEX.COM/C7



C8000 LAB ANALYZER

More at CADEX.COM/C8



Not what you're looking for? We have also a selection of over 3,200 different custom-made adapters for almost any battery type. Or inquire us to develop your own. Learn more at Cadex.com/adapters



YOUR LIFE. EMPOWERED

Specifications

COMPATIBILITY	Works with the Cadex 7200, 7200-C, 7400, C7400-C, C7400ER, and C7400ER-C battery analyzers. (May also be used on the C5100, C8000, C7000 for NiCd, NiMH and SLA batteries only).	ELECTRICAL	16kb non-volatile memory. Battery settings (C-Code) are entered through the analyzer. The battery parameters are stored in the adapter. Each Cadex UBA holds 10 unique C-Codes.
MECHANICAL	SnapLock™ Design, interchangeable with custom battery adapters.	BATTERY TYPES	Lithium Ion/Polymer, Nickel Metal Hydride, Nickel Cadmium, Lead Acid.
CONTACTS	RigidArm: Gold plated contacts*, rated at 3A FlexArm: Gold plated contacts*, rated at 3A Smart Cable: Two alligators, red and black, connected by banana plugs; rated at 3A	WARRANTY	Cadex warrants against defective materials and workmanship for 1 year from purchase date. (2years when purchased with a Cadex analyzer) * Field replaceable

DISTRIBUTED BY :



CADEX ELECTRONICS, INC
VISIT CADEX.COM/ADAPTERS FOR MORE INFORMATION
ENQUIRIES: INFO@CADEX.COM

@CADEXELECTRONIC

